




Pen size cylinder—PB Series

Compendium of PB Series



Criteria for selection: Cylinder thrust

Unit : Newton(N)

Bore size	Rod size	Acting type	Pressure area(mm ²)	Operating pressure(MPa)						
				0.1	0.2	0.3	0.4	0.5	0.6	0.7
4	2	Single acting_Push side	12.6	-	-	1.6	2.8	4.1	5.3	6.6
		Double Push side	12.6	1.3	2.5	3.8	5.0	6.3	7.6	8.8
		Double Pull side	9.4	0.9	1.9	2.8	3.8	4.7	5.6	6.6
		Single Push side	28.3	-	-	5.0	7.8	10.6	13.5	16.3
6	3	Single Pull side	21.2	-	-	2.9	5.0	7.1	9.2	11.3
		Double Push side	28.3	2.8	5.7	8.5	11.3	14.2	17.0	19.8
		Double Pull side	21.2	2.1	4.2	6.4	8.5	10.6	12.7	14.8
		Single Push side	50.3	-	3.6	8.6	13.6	18.7	23.7	28.7
8	4	Single Pull side	37.7	-	1.0	4.8	8.6	12.4	16.1	19.9
		Double Push side	50.3	5.0	10.1	15.1	20.1	25.2	30.2	35.2
		Double Pull side	37.7	3.8	7.5	11.3	15.1	18.9	22.6	26.4
		Single Push side	78.5	-	6.2	14.1	21.9	29.8	37.6	45.5
10	4	Single Pull side	65.9	-	3.7	10.3	16.9	23.5	30.1	36.7
		Double Push side	78.5	7.9	15.7	23.6	31.4	39.3	47.1	55.0
		Double Pull side	65.9	6.6	13.2	19.8	26.4	33.0	39.5	46.2
		Single Push side	113.0	-	9.0	20.3	31.6	42.9	54.2	65.5
12	5	Single Pull side	93.4	-	5.1	14.4	23.8	33.1	42.4	51.8
		Double Push side	113.0	11.3	22.6	33.9	45.2	56.5	67.8	79.1
		Double Pull side	93.4	9.3	18.7	28.0	37.4	46.7	56.0	65.4
		Single Push side	201.0	-	14.5	34.6	54.7	74.8	94.9	115.0
16	5	Single Pull side	181.3	-	10.6	28.7	46.8	65.0	83.1	101.2
		Double Push side	201.0	20.1	40.2	60.3	80.4	100.5	120.6	140.7
		Double Pull side	181.3	18.1	36.3	54.4	72.5	90.7	108.8	126.9

Installation and application




- When load changes in the work, the cylinder with abundant output capacity shall be selected.
- Relative cylinder with high temperature resistance or corrosion resistance shall be chosen under the condition of high temperature or corrosion.
- Necessary protection measure shall be taken in the environment with higher humidity, much dust or water drops, oil dust and welding dregs.
- Dirty substances in the pipe must be eliminated before cylinder is connected with pipeline to prevent the entrance of particles into the cylinder.
- The medium used by cylinder shall be filtered to 40μm or below.
- Anti-freezing measure shall be adopted under low temperature environment to prevent moisture freezing.
- The load of the cylinder with the diameter of Φ4 needs to be coaxial with the cylinder to avoid side load, otherwise, piston rod will be bent and deformed and damage the thread at the end of the rod. Single-acting type can not be added in return.
- If the cylinder is dismantled and stored for a long time, Please to conduct anti-rust treatment to the surface. Anti-dust caps shall be added in air inlet and outlet ports. The front and back cover can not be dismantled, which shall be especially noticed.

Pen size cylinder

PB Series



Symbol



Product feature

1. JIS standard is implemented.
2. It belongs to mini cylinder that has compact structure, small volume and light weight.
3. The guide precision of piston rod is high and no additional lubricant is needed.
4. PB4 and PB6 can only be front mounted. PB10, PB12 and PB16 has the flexibility of both front and rear mount.
5. Piston rod and cylinder body with the material of stainless steel make the cylinder adapt general working environment with corrosivity.
6. There are cylinders and accessories with several specifications for installation for your choice.
7. It has small cylinder diameter and quick reaction, suitable for the working environment with higher frequency.

Ordering code

Specification


Bore size(mm)		4	6	10	12	16
Acting type		Double acting, Single acting_Push		Double acting, Single acting		
Fluid		Air(to be filtered by 40μm filter element)				
Operating pressure	Double acting	0.2~0.7MPa(28~100psi)(2.0~7.0bar)		0.15~0.7MPa(22~100psi)(1.5~7.0bar)		
	Single acting	0.3~0.7MPa(45~100psi)(3.0~7.0bar)		0.2~0.7MPa(28~100psi)(2.0~7.0bar)		
Proof pressure		1.2MPa(175psi)(12bar)				
Temperature °C		-20~70				
Speed range mm/s		50~500		50~800		
Stroke tolerance		+0.5 0		0~150 ^{+1.0} ₀ >150 ^{+1.5} ₀		
Cushion type		No cushion		Bumper		
Port size		Tube		M5×0.8		

Add) Refer to P362 for detail of sensor switch.

Stroke

Bore size (mm)	Standard stroke (mm)		Max.std stroke	Max. stroke
PB	4	5 10 15 20	20	20
	6	10 15 20 25 30 40 50 60	60	60
	10	10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	200
	12	10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	300
	16	10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200 250 300	300	300
PBD	6	5 10 15 20 25 30 40 50	50	-
PBD	10	10 15 20 25 30 40 50 60 75 80 100	100	-
PBJ	12	10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	-
	16	10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	-
PSB	4	5 10 15 20	-	-
	6	5 10 15 20 25 30 40 50 60	-	-
PSB	10	5 10 15 20 25 30 40 50 60	-	-
PTB	12	5 10 15 20 25 30 40 50 60	-	-
	16	5 10 15 20 25 30 40 50 60	-	-

[Note] Consult us for non-standard stroke.



① Model	② Bore size	③ Stroke	④ Adjustable stroke	⑤ Magnet	⑥ Back cover	⑦ Mounting type[Note1]
PB: Pen size cylinder (Double acting)	4	Refer to stroke table for details	No this code	Blank: Without magnet S: With magnet	Model	Model
PSB: Pen size cylinder (Single acting_push)	6				PB	Blank: No accessories
	10				PSB	FA: FA type
	12				PTB	LB: LB type
	16				PBD	CJ: CJ type
PTB: Pen size cylinder (Single acting_pull)	6	Refer to stroke table for details	No this code	Blank: Without magnet S: With magnet	PB	Blank: No accessories
PBD: Pen size cylinder (Double rod)	10				PSB	FA: FA type
	12				PTB	LB: LB type
	16				PBD	CJ: CJ type
PBJ: Pen size cylinder (Adjustable stroke)	10				PBD	Blank: No accessories
	12				PBJ	FA: FA type
	16				PBJ	LB: LB type

[Note1] Please refer to page 73 for accessory parts.


AirTAC

Pen size cylinder


PB Series

PBD

Φ6




Φ10-Φ16



PBJ

Φ10-Φ16



Bore size\Item	A		AB	AC	AD	B	D	DA	DB	E	EA	EB	F	FA	G	GA	M	MA	P	PA
Model	PBD	PBJ																		
10	104	99	28	48	11.5	12	4	20	15	M4×0.7	15	16.5	7	3	11	4	M8×1.0	8	M5×0.8	7.5
12	104	101	28	48	11.5	15	5	20	17	M5×0.8	15	16.5	8	4	14	4	M10×1.0	8	M5×0.8	7.5
16	107	104	28	51	12	18	5	20	17	M5×0.8	15	16.5	8	4	14	4	M10×1.0	8	M5×0.8	7.5


Remark : The dimensions of magnet type cylinder are the same as non-magnet type cylinder.

Pen size cylinder

PBR Series



Symbol



Product feature

1. JIS standard is implemented.
2. It belongs to mini cylinder that has compact structure, small volume and light weight.
3. The guide precision of piston rod is high and no additional lubricant is needed.
4. Screw holes are designed for mounting directly at the front cover without any accessories.
5. Piston rod stainless steel barrel make the cylinder adapt general corrosive working environment.
6. It has small cylinder diameter and quick reaction, suitable for the working environment with higher frequency.

Specification

Bore size(mm)		6	8	10	12	16
Acting type		Double acting、Single acting				
Fluid		Air(to be filtered by 40μm filter element)				
Operating pressure	Double acting	0.15~0.7MPa(22~100psi)(1.5~7.0bar)				
	Single acting	0.3~0.7MPa(45~100psi)(3.0~7.0bar) 0.2~0.7MPa(28~100psi)(2.0~7.0bar)				
Proof pressure		1.2MPa(175psi)(12bar)				
Temperature °C		-20~70				
Speed range mm/s		50~800				
Stroke tolerance		0~150 ^{+1.0} ₀ >150 ^{+1.5} ₀				
Cushion type		Bumper				
Port size		M5×0.8				

Add) Refer to P362 for detail of sensor switch.

Stroke

Bore size (mm)	Standard stroke (mm)	Max.std stroke	Max. stroke
PBR	6 10 15 20 25 30 40 50 60	60	60
	8 10 15 20 25 30 40 50 60 75 80 100 125 150	150	200
	10 10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	200
	12 10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200	200	300
	16 10 15 20 25 30 40 50 60 75 80 100 125 150 160 175 200 250 300	300	300
PSBR PTBR	6 5 10 15 20 25 30 40 50 60	-	-
	8 5 10 15 20 25 30 40 50 60	-	-
	10 5 10 15 20 25 30 40 50 60	-	-
	12 5 10 15 20 25 30 40 50 60 75	-	-
	16 5 10 15 20 25 30 40 50 60 75 100	-	-

[Note] Consult us for non-standard stroke.

Ordering code


PBR 16 ×30 S U




① Model	② Bore size	③ Stroke	④ Magnet	⑤ Back cover		
PBR: Pen size cylinder(Double acting)	6	Refer to stroke table for details	Blank: Without magnet S: With magnet	Model	Back cover	Bore size
PSBR: Pen size cylinder (Single acting_push)	8			PBR	U: Perpendicular 90°	Φ8~Φ16
PTBR: Pen size cylinder(Single acting_pull)	10			PSBR	R: Axial air-in	Φ6~Φ16
	12			PTBR	R: Axial air-in	Φ6~Φ16
	16					

Mounting type

Top bolt mounting



Bottom bolt mounting




Note: Select appropriate bolt based on actual working conditions when mounting from the bottom.

Pen size cylinder

PBR Series

Inner structure and material of major parts

Double acting with magnet




NO.	Item	Material	NO.	Item	Material
1	Rod nut	Carbon steel	8	Piston seal	NBR
2	Piston rod	SUS304	9	Magnet	Sintered metal(Neodymium-iron-boron)
3	Front cover O-ring	NBR	10	Magnet washer	NBR
4	Front cover	Aluminum alloy	11	Magnet holder	SUS303/Aluminum alloy
5	Barrel	SUS316L	12	Wear ring	Wear resistant material
6	Bumper	TPU	13	Bumper	TPU
7	Piston	SUS303/Aluminum alloy	14	Back cover	Aluminum alloy


Note: inner structure & material data sheet is based on certain bore size.
Please contact AirTAC if you need inner structure & material data sheet for specific bore size.

Dimensions


PBR



R Type
(Axial air-in)




U Type
(Perpendicular 90°)




Bore size\Item	A	AB	AC	AD	AE	B	BA	C	CA	D	E	EA	EB	F	FA	J	JA	K	KA	L	LA	LB	P	PA	PB	R
6	70	20	50	19	7	17	10	14	7	3	M3×0.5	15	16	5.5	2.4	6.5	4	M4×0.7	7	3.3	8	10	M5×0.8	14	-	11
8	74	20	54	19.5	9.5	19	12	16	8	4	M4×0.7	15	16.5	7	3	6.5	4	M4×0.7	7	3.3	8	12	M5×0.8	15	5	14
10	74	20	54	19.5	9.5	19	12	16	8	4	M4×0.7	15	16.5	7	3	6.5	4	M4×0.7	7	3.3	8	12	M5×0.8	15.5	5	14
12	74	20	54	19.5	9.5	24	15	20	10	5	M5×0.8	15	16.5	8	4	8	5	M5×0.8	8	4.3	8	16	M5×0.8	15.5	5	17
16	76	20	56	20	9.5	24	18	20	10	6	M5×0.8	15	16.5	8	4	8	5	M5×0.8	8	4.3	8	16	M5×0.8	15.5	5	20

Remark: The dimensions of magnet type cylinder are the same as non-magnet type cylinder. Only axial air intake type of back cover is available for Φ6mm bore size.


PSBR




R Type
(Axial air-in)




U Type
(Perpendicular 90°)



PTBR



R Type
(Axial air-in)



Bore size\Item		A												AC																	
Model		PSBR						PTBR						PSBR						PTBR											
Stroke		5~15	16~30	31~45	46~60	61~75	76~100	5~15	16~30	31~45	46~60	61~75	76~100	5~15	16~30	31~45	46~60	61~75	76~100	5~15	16~30	31~45	46~60	61~75	76~100	5~15	16~30	31~45	46~60	61~75	76~100
6		70	79	83	97	-	-	74.5	83.5	87.5	101.5	-	-	50	59	63	77	-	-	54.5	63.5	67.5	81.5	-	-	-	-	-	-	-	-
8		76.5	82.5	93.5	101.5	-	-	78.5	84.5	95.5	103.5	-	-	56.5	62.5	73.5	81.5	-	-	58.5	64.5	75.5	83.5	-	-	-	-	-	-	-	-
10		73.5	81	93	105	-	-	76.5	84	96	108	-	-	53.5	61	73	85	-	-	56.5	64	76	88	-	-	-	-	-	-	-	-
12		73.5	81	93	105	111.5	-	76.5	84	96	108	114.5	-	53.5	61	73	85	91.5	-	56.5	64	76	88	94.5	-	-	-	-	-	-	-
16		74.5	83	95	107	113	119	77.5	86	98	110	116	122	54.5	63	75	87	93	99	57.5	66	78	90	96	102	-	-	-	-	-	-
Bore size\Item		AD				AE																									
Model		PSBR		PTBR	AB	PSBR		PTBR	B	BA	C	CA	D	E	EA	EB	F	FA	J	JA	K	KA	L	LA	LB	P	PA	PB	R		
6		13	13	19	20	7	5	17	10	14	7	3	M3×0.5	15	16	5.5	2.4	6.5	4	M4×0.7	7	3.3	8	10	M5×0.8	14	-	11	-		
8		13	13	19.5	20	9.5	5	19	12	16	8	4	M4×0.7	15	16.5	7	3	6.5	4	M4×0.7	7	3.3	8	12	M5×0.8	15	5	14	-		
10		13	13	19.5	20	9.5	5	19	12	16	8	4	M4×0.7	15	16.5	7	3	6.5	4	M4×0.7	7	3.3	8	12	M5×0.8	15.5	5	14	-		
12		13	13	19.5	20	9.5	5	24	15	20	10	5	M5×0.8	15	16.5	8	4	8	5	M5×0.8	8	4.3	8	16	M5×0.8	15.5	5	17	-		
16		13	13	20	20	9.5	5	24	18	20	10	6	M5×0.8	15	16.5	8	4	8	5	M5×0.8	8	4.3	8	16	M5×0.8	15.5	5	20	-		

Remark: The dimensions of magnet type cylinder are the same as non-magnet type cylinder. Only axial air intake type of back cover is available for Φ6mm bore size.

Pen size cylinder

PB Series—Accessories

List for ordering code of accessories

Accessories Bore size	Mounting accessories			Knuckle				Sensor switch		
	LB	FA	CJ	I	Y	F	U	CMSG	DMSG	EMSG
4	-	-	-	-	-	-	-	-	-	-
6	F-PB6LB	F-PB6FA	-	F-PB6I	F-PB6Y	F-M3X040F	-	CMSG	DMSG	EMSG
10	F-PB10LB	F-PB10FA	F-PB10CJ	F-PB10I	F-PB10Y	F-M4X070F	F-M4X070U			
12	F-PB12LB	F-PB12FA	F-PB12CJ	F-PB12I	F-PB12Y	F-M5X080F	F-M5X080U			
16			F-PB16CJ							

Accessory selection

Accessories Cylinder model		Mounting accessories			Knuckle				Sensor switch		
		LB	FA	CJ	I	Y	U[1]	F	CMSG	DMSG	EMSG
PB	Standard	•	•	•	•	•	•	•	x	x	x
	With magnet	•	•	•	•	•	•	•	•	•	•
PSB	Standard	•	•	•	•	•	•	•	x	x	x
PTB	With magnet	•	•	•	•	•	•	•	•	•	•
PBD	Standard	•	•	x	•	•	•	•	x	x	x
PBJ	With magnet	•	•	x	•	•	•	•	•	•	•

Material of accessories


Accessories Bore size	Mounting accessories			Knuckle			
	LB	FA	CJ	I	Y	F	U
4~16	△	△	△	□	□	□	□

△—SPCC ; □—Carbon steel ;

[Note1] Please refer to P358~361 for knuckle detail.


Dimensions

LB




Bore size\Item	A	B	BB	C	CC	D	E	F	G	I
6	24	28	32	56.5	9	16.5	5	7	4.5	1.5
10	24	28	32	53	9	16.5	5	7	4.5	2
12	33	28	42	55	14	25	6	9	5.5	2.5
16	33	28	42	57	14	25	6	9	5.5	2.5

FA



Bore size\Item	A	B	BB	C	CC	D	E	F
6	24	28	32	49.5	14	1.5	4.5	6.3
10	24	28	32	46	14	2	4.5	8.2
12	33	28	42	46	20	3	5.5	10.2
16	33	28	42	48	20	3	5.5	10.2


CJ



Bore size\Item	A	B	C	D	E	F	G	H	I	J	K	L
10	82	22	54	40	4.5	29	21	12	2	18	9.1	32
12	84	28	56	48	5.5	35	25	16	2.5	20.4	14.1	38
16	86	28	58	48	5.5	35	25	16	2.5	20.4	14.1	38


[Note] CJ type accessory includes I knuckle and PIN. It need to be matched with I knuckle and with relevant PIN.

I Knuckle



Bore size\Item	A	B	C	D	E	F	G	H
F-PB6I	M3×0.5	6	3	3	12	5	5	5
F-PB10I	M4×0.7	12	3.3	3	21	9.1	7.5	8
F-PB12I	M5×0.8	12	5	6.3	25	14.1	7.5	12

Y Knuckle



Bore size\Item	A	B	C	D	E	F	G	H	I
F-PB6Y	15.5	12	5	6	M3×0.5	6	9	3	3
F-PB10Y	28	21	10.2	12	M4×0.7	10	15.5	3.2	3.3
F-PB12Y	28	21	10.2	12	M5×0.8	10	15.5	6.5	5